

# Klemsan®

## 304121 AVK 2,5

2,5mm<sup>2</sup>, screw type, single deck feed through terminal block, Insulating material PA, Blue

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	100
	Weight (g)	
<b>Dimensions</b>	Width	5 mm
	Length	44.2 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.5 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm <sup>2</sup>
	Norm	EN 60947-7-1
<b>VDE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm <sup>2</sup>
	VDE Norm	IEC 60947-7-1
<b>UL / CSA Technical Data</b>	Nominal Voltage	600 V ~
	Nominal Current	20 A
	Cross Section	AWG/26-12
<b>ATEX Technical Data</b>	Nominal Voltage	630 V ~
	Nominal Current	21 A
	Cross Section	2.5
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>

Maximum solid Strand cross section	4 mm <sup>2</sup>
Minimum fine Strand cross section	1.5 mm <sup>2</sup>
Maximum fine strand cross section	2.5 mm <sup>2</sup>
AWG Conductor Range	26-12
Connection Type	screw/vidalı
Insulation Stripping length	10 mm
Tightening torque	0.4 Nm



Alçak Gerilim direktiflerine uygunluk belgesi - VDE Certificate

Türk Standartlarına Uygunluk Belgesi - TSE Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

CSA - CE Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate



Rusya Onaylı Denizcilik Sertifikası - Rusya Denizcilik Certificate

EAC - Russian EAC

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

#### Order Info

304120	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Grey
304121	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Blue
304122	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Green
304123	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Yellow
304124	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Red
304129	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Beige
304125	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Black

<b>Order Info</b>	
 304126	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,White
 304127	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Orange
 304128	2,5mm <sup>2</sup> ,screw type,single deck feed through terminal block,Insulation material PA,Brown