





HOUSING	OPERATING DISTANCE	MOUNTING	✓ Long sensing range ✓ Outstanding accuracy and temperature stability ✓ Resolution in μm range	
M30	40 mm	Non-embeddable	✓ Exceptional price-performance ratio ✓ Current or voltage output ✓ IP67	




DW-AD-519-M30



DW-AD-519-M30-120



DW-AS-519-M30-002



DW-AS-519-M30-120

DETECTION DATA		INTERFACE	
Sensing distance (S_d)	40 mm	IO-Link	✗
Repeat accuracy (IEC 60947-5-2)	± 0.35 mm	MTTF (@40°C)	546 y
Static resolution* (@0.67· S_d)	≤ 1.42 μm		
Dynamic resolution* (@0.67· S_d)	≤ 5.5 μm		
Temperature drift of S_d	$\leq 5\%$ (0... +70°C) $\leq 10\%$ (-25... 0°C)		
Standard target	120 x 120 x 1 mm ³ , FE360		

*Static resolution is measured when the target is moving at 20 Hz. Dynamic resolution when the target is moving at the sensor bandwidth limit.

ELECTRICAL DATA		MECHANICAL DATA	
Supply voltage range (U_b)	10...30 VDC	Mounting	Non-embeddable
Residual ripple	$\leq 20\%$ U_b	Housing material	Chrome-plated brass
Power consumption (no-load)	≤ 12 mA	Sensing face material	PBTP
Max. load at voltage output	≤ 10 mA	Max tightening torque	70 Nm
Max. load at current output	1k Ω ($U_b=10\text{V}$) / 5k Ω ($U_b=30\text{V}$)	Ambient operating temperature	-25...+70°C
Bandwidth	100 Hz	Enclosure rating	IP67
Time delay before availability	20 ms	Weight (cable / connector)	see page 2
Recovery time	10 ms	Shock and vibration	IEC 60947-5-2 / 7.4
Short-circuit protection	✓		
Voltage reversal protection	✓		
Cable length max.	≤ 300 m		


Note: all data measured according to IEC 60947-5-2 standard with $U_b = 20 \dots 30\text{VDC}$, $T_A = 23^\circ\text{C} \pm 5^\circ\text{C}$.

CORRECTION FACTORS

Steel FE 360	1	Copper	0.4	Aluminum	0.44	Brass	0.49	Stainless S. V2A 1 / 2 mm	0.76
--------------	---	--------	-----	----------	------	-------	------	---------------------------	------

Note: the operating distance of the sensor must be multiplied by the correction factor of the material. For example, the operating distance on Aluminum is $S_{n, Al} = S_n \times CF_{Al}$. In case of embeddable mounting, the distance is multiplied by the additional correction factor of the support, thus $S_{n, Al} = S_n \times CF_{Al} \times CF_{emb, Al}$.

INSTALLATION CONDITIONS




A : metal free zone
B : sensing face
C : support

a : 55 mm
b : 150 mm
c : 120 mm

d : steel 35 mm
alu 25 mm
brass 25 mm
stainless steel 20 mm

Note: additional installation information can be found in the glossary of the Contrinex General Catalog.


RESPONSE DIAGRAM




Output voltage	s = 0 mm	0 V / -0.0 +0.2 V
	s = $S_d/2$ mm	2.6 V $\pm$ 0.2 V
	s = S_d mm	5.0 V $\pm$ 0.2 V
	s > S_d mm	5...6 V $\pm$ 0.2 V

Output current	s = 0 mm	1 mA $\pm$ 0.2 mA
	s = $S_d/2$ mm	3.1 mA $\pm$ 0.2 mA
	s = S_d mm	5 mA $\pm$ 0.2 mA
	s > S_d mm	5...5.75 mA $\pm$ 0.2 mA

WIRING DIAGRAM



PIN ASSIGNMENT



AVAILABLE TYPES

Part number	Part reference	Connection	Output on pin 2 / wh	Output on pin 4 / bk	Weight
330-020-432	DW-AD-519-M30	PUR, 2 m, 4 wire	1...5 mA	0...5 V	215 g
330-020-433	DW-AD-519-M30-120	PUR, 2 m, 4 wire	1...5 mA	0...5 V	190 g
330-020-458	DW-AS-519-M30-002	M12 4-pin	1...5 mA	0...5 V	155 g
330-020-459	DW-AS-519-M30-120	M12 4-pin	1...5 mA	0...5 V	135 g

Note: part reference may include additional suffix to indicate a revision version or special version. Further information is available on request.

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines. Terms of delivery and rights to change design reserved.